

**PRODUCT DATA SHEET**  
**HEXAGONAL ZINC ANODES**  
**For Electroplating**

**1. DIMENSIONS:**

Length of the diagonal (mm)	Thickness (mm)
19 (ref.)	7.5 ± 0.5 (ref.)

**2. CHEMICAL COMPOSITION:**

Hexagonal Zinc Anodes for electroplating are produced from SHG ZINC (Norm BS EN 1179:2003 / Norm ASTM B6-03).

Element	%
Pb	Max. 0,003
Cd	Max. 0,003
Fe	Max. 0,002
Sn	Max. 0,001
Cu	Max. 0,001
Al	Max. 0,001
Zn	Min. 99,995

Total impurities ≤ 0,005 %

### 3. STANDARD PACKAGING:

- 40 polypropylene sacks of 25 kg each, arranged on a wooden pallet which complies with ISPM norm N° 15, secured with plastic straps and wrapped with stretch film.
- Big bags of 200 kg each, arranged on wooden pallets which comply with ISPM norm N° 15, secured with plastic straps and wrapped with stretch film.
- Big bags of 1mt each, arranged on wooden pallets which comply with ISPM norm N° 15, secured with plastic straps and wrapped with stretch film.



### 4. STORAGE:

- Store the product in a dry and covered area.